


HBR3-00-160-X-B-24V

Lighting Dimension



Mechanical Information	
Casing Material	Aluminium
Storage & Operating Temperature Range	Temp 0-60°C, Humidity 20-85%
Weight	1105 g
Length / Outer Diameter	173 mm
Width / Inner Diameter	34 mm
Thickness / Height	31 mm



HBR3-00-160-X-B-24V

Optical Information				
Part Number		HBR3-00-160-X-B-24V		
LED Colour		BLUE		
Wavelength	(nm)	470		
Intensity (±15%)	(Lux)	3892	2202	1542
Working Distance	(mm)	250	350	450
Illumination (number of rows)		X		
Illumination Active Area				
Active Length / Outer Diameter	(mm)	134		
Active Width / Inner Diameter	(mm)	36.6		
Emission Angle	(deg.)	0		
Eye Safety Class (IEC62471)		II		
Electrical Information				
Lighting Supply Voltage (constant voltage mode)		24V ± 2%		
Continuous Current	(mA)	340		
Power Consumption	(W)	8.16		
Lighting Casing Temperature, Operating after 60 minutes	°C	48.9		
Strobe Mode Specification				
Pulse Operation		YES		
Max. Lighting Supply Voltage (constant voltage power supply)	(V)	Pulsing at 24VDC to 48VDC, 0-10% Duty Cycle Recommended at 36VDC		
Pulse Current, (Max. 10 msec) (constant current power supply)	(mA)	1020		
Max. Trigger Pulse Duration	(msec)	10		
Duty Cycle		0-10%		
Additional Information				
Additional Cooling Method		Attached to machine part for better heat dissipation		
Intensity Controller Selection		SD / SDA-Series		
CE Conformity		YES		
RoHS Compliance		YES		
Connection				
Connector Type (default)		M12 5 PIN CONNECTOR (MALE)		
Cable Length (out from lighting)	(mm)	700		
Pin Configuration		Pin	Signal	Cable Colour
		1	24V	BROWN
		2	-	WHITE
		3	GND	BLUE
		4	-	BLACK
		5	-	GRAY
Extension Cable				
Connector Type (default)		M12 5 PIN CONNECTOR (FEMALE)		
Part Number		EXT-FL-M12F-3M-24V		
Cable Length (out from female connector)	(mm)	3000		
Extension Cable (connect to M12 5 Pin Male Connector from lighting)				
Application				
Illumination Type		Direct Illumination of High Luminosity Square Spotlight		
Application Use		General illumination, label inspection, character inspection, code recognition, robotic picking, inspection for parts identification & missing parts, visual inspection for large workpiece, measuring stamp dimensions for press products.		

HBR3-00-160-X-B-24V

Advantages	Join Bracket (Angle Mount)	L-bracket (Vertical Mount)	L-shaped Plate (Horizontal Mount)
Easy Mounting	