


## HBBX-00-160X240-X-R-24V

### Lighting Dimension






Mechanical Information	
Casing Material	Aluminium
Storage & Operating Temperature Range	Temp 0-60°C, Humidity 20-85%
Weight	1500 g
Length / Outer Diameter	266.2 mm
Width / Inner Diameter	186.2 mm
Thickness / Height	43 mm



## HBBX-00-160X240-X-R-24V

Optical Information			
Part Number	HBBX-00-160X240-X-R-24V		
LED Colour	RED		
Wavelength	(nm)	630	
Intensity ( ±15%)	(Lux)	7740	7068 6372
Working Distance	(mm)	10	20 30
Illumination (number of rows)	X		
Illumination Active Area			
Active Length	(mm)	227	
Active Width	(mm)	147	
Emission Angle	(deg.)	0	
Eye Safety Class ( IEC62471)	EXEMPT		
Electrical Information			
Lighting Supply Voltage (constant voltage mode)	24V ± 2%		
Continuous Current	(mA)	720	
Power Consumption	(W)	17.28	
Lighting Casing Temperature, Operating after 60 minutes	°C	47.7	
Strobe Mode Specification			
Pulse Operation	YES		
Max. Lighting Supply Voltage (constant voltage power supply)	(V)	Pulsing at 24VDC to 48VDC, 0-10% Duty Cycle Recommended at 36VDC	
Pulse Current, (Max. 10 msec) (constant current power supply)	(mA)	2160	
Max. Trigger Pulse Duration	(msec)	10	
Duty Cycle	0-10%		
Additional Information			
Additional Cooling Method	Attached to machine part for better heat dissipation		
Intensity Controller Selection	SD/SDA-Series		
CE Conformity	YES		
RoHS Compliance	YES		
Connection			
Connector Type (default)	M12 5 PIN CONNECTOR (MALE)		
Cable Length (out from lighting)	( mm )	700	
Pin Configuration	Pin	Signal	Cable Colour
	1	24V	BROWN
	2	-	WHITE
	3	GND	BLUE
	4	-	BLACK
	5	-	GRAY
Extension Cable			
Connector Type (default)	M12 5 PIN CONNECTOR (FEMALE)		
Part Number	EXT-FL-M12F-3M-24V		
Cable Length (out from female connector)	(mm)	3000	
Extension Cable (connect to M12 5 Pin Male Connector from lighting)			
Application			
Illumination Type	Backlight Illumination		
Application Use	Lead frame inspection, shape recognition, size measurement		

## HBBX-00-160X240-X-R-24V

<p><b>Advantages</b></p>			
<p>PCBA Cascade</p>			
<p>Easy Mounting</p>	<p>Join Bracket (Angle Mount)</p> 	<p>L Bracket (Vertical Mount)</p> 	<p>L-shaped Plate (Horizontal Mount)</p> 