


IPE-80X180-LSW-15-2-R-XXX-XXXX-X

Lighting Dimension



Mechanical Information	
Casing Material	Aluminium
Storage & Operating Temperature Range	Temp 0 - 45°C, Humidity 20-85%
Weight	1409 g
Length / Outer Diameter	82.5 mm
Width / Inner Diameter	28 mm
Thickness / Height	218 mm



IPE-80X180-LSW-15-2-R-XXX-XXXX-X

Optical Information				
Part Number		IPE-80X180-LSW-15-2-R-XXX-XXXX-X		
LED Colour		RED		
Wavelength	(nm)	630		
Intensity (±15%)	(Lux)	38600	31000	26200
Working Distance	(mm)	59	64	69
Illumination (number of rows)		2		
Illumination Active Area				
Active Length	(mm)	40		
Active Width	(mm)	28.8		
Emission Angle	(deg.)	15		
Eye Safety Class (IEC62471)		EXEMPT		
Electrical Information				
Lighting Supply Voltage (constant voltage mode)		24V ± 2%		
Continuous Current	(mA)	165		
Power Consumption	(W)	1.98		
Lighting Casing Temperature, Operating after 60 minutes	°C	62.1		
Strobe Mode Specification				
Pulse Operation		YES		
Max. Lighting Supply Voltage (constant voltage power supply)	(V)	Pulsing at 24VDC to 48VDC, 0-10% Duty Cycle, Recommended at 36VDC		
Pulse Current, (Max. 10 msec) (constant current power supply)	(mA)	495		
Max. Trigger Pulse Duration	(msec)	10		
Duty Cycle		0-10%		
Additional Information				
Additional Cooling Method		Attached to machine part for better heat dissipation		
Intensity Controller Selection		SD and SDA-Series		
CE Conformity		YES		
RoHS Compliance		YES		
Connection				
Connector Type (default)		M12 5 PIN CONNECTOR (MALE)		
Cable Length (out from lighting)	(mm)	700		
Pin Configuration		Pin	Signal	Cable Colour
		1	24V	BROWN
		2	-	WHITE
		3	GND	BLUE
		4	-	BLACK
		5	-	GRAY
Extension Cable				
Connector Type (default)		M12 5 PIN CONNECTOR (FEMALE)		
Part Number		EXT-FL-M12F-3M-24V		
Cable Length (out from female connector)	(mm)	3000		
Extension Cable (connect to M12 5 Pin Male Connector from lighting)				
Application				
Illumination Type		Direct Illumination		
Application Use		substrate inspection, label inspection, flat surface, fiducially recognition.		