


HIDS-00-200-X-R-24V

Lighting Dimension




Mechanical Information	
Casing Material	Aluminium
Storage & Operating Temperature Range	Temp 0-60°C, Humidity 20-85%
Weight	2160 g
Outer Dimension	268 x 268 mm
Inner Diameter	50 mm
Thickness	143.6 mm



HIDS-00-200-X-R-24V

Optical Information				
Part Number		HIDS-00-200-X-R-24V		
LED Colour		RED		
Wavelength	(nm)	630		
Intensity (±15%)	(Lux)	4779	4293	3861
Working Distance	(mm)	87	97	107
Illumination (number of rows)		1		
Illumination Active Area				
Active Outer Diameter	(mm)	160		
Active Inner Diameter	(mm)	50		
Emission Angle	(deg.)	0		
Eye Safety Class (IEC62471)		EXEMPT		
Electrical Information				
Lighting Supply Voltage (constant voltage mode)		24V ± 2%		
Continuous Current	(mA)	780		
Power Consumption	(W)	18.72		
Lighting Casing Temperature, Operating after 60 minutes	°C	41.5		
Strobe Mode Specification				
Pulse Operation		YES		
Max. Lighting Supply Voltage (constant voltage power supply)	(V)	Pulsing at 24VDC to 48VDC, 0-10% Duty Cycle Recommended at 36VDC		
Pulse Current, (Max. 10 msec) (constant current power supply)	(mA)	2340		
Max. Trigger Pulse Duration	(msec)	10		
Duty Cycle		0-10%		
Additional Information				
Additional Cooling Method		Attached to machine part for better heat dissipation		
Lifespan in Continuous Mode		20,000 hours (drop to 50% intensity) at 25°C		
Lifespan in Strobe Mode		Est. >50,000 hours (drop to 50% intensity) at 25°C		
Intensity Controller Selection		SD/SDA-Series		
CE Conformity		YES		
RoHS Compliance		YES		
Connection				
Connector Type (default)		M12 5 PIN CONNECTOR (MALE)		
Cable Length (out from lighting)	(mm)	700		
Pin Configuration		Pin	Signal	Cable Colour
		1	24V	BROWN
		2	-	WHITE
		3	GND	BLUE
		4	-	BLACK
		5	-	GRAY
Extension Cable				
Connector Type (default)		M12 5 PIN CONNECTOR (FEMALE)		
Part Number		EXT-FL-M12F-3M-24V		
Cable Length (out from female connector)	(mm)	3000		
Extension Cable (connect to M12 5 Pin Male Connector from lighting)				
Application				
Illumination Type		Indirect Dome Illumination		
Application Use		Crack, chip, stains on circular or cylindrical objects, solder inspection and substrate inspection		

HIDS-00-200-X-R-24V

Advantages	
Flexible Illuminator	<div data-bbox="724 349 836 367">Full Dome Cover</div> <div data-bbox="1158 349 1270 367">Half Dome Cover</div> 
Easy Mounting	